

XINGLONG CONTAINER CONVENTIONAL STAINLESS STEEL VERTICAL PRODUCT PARAMETER TABLE (LOW PRESSURE)

兴隆容器
 常规不锈钢立式产品参数表（低压）

TYPE NUMBER (ENGINEERING VOLUME/ WORKING PRESSURE) 型 号 (工程容积/ 工作压力)	TOTAL CONTAINER HEIGHT 容 器 总 高 (H)mm	NOMINAL DIAMETER 公 称 直 径 (DN)	AIR INTAKE DIAMETER 进 气 口 通 径	AIR OUTLET DIAMETER 出 气 口 通 径	SAFETY VALVE CONNECTION 安 全 阀 接 口	BLOWDOWN VALVE CONNECTION 排 污 阀 接 口	PRESSURE GAUGE CONNECTION 压 力 表 接 口	TYPE NUMBER (ENGINEERING VOLUME/ WORKING PRESSURE) 型 号 (工程容积/ 工作压力)	TOTAL CONTAINER HEIGHT 容 器 总 高 (H)mm	NOMINAL DIAMETER 公 称 直 径 (DN)	AIR INTAKE DIAMETER 进 气 口 通 径	AIR OUTLET DIAMETER 出 气 口 通 径	SAFETY VALVE CONNECTION 安 全 阀 接 口	BLOWDOWN VALVE CONNECTION 排 污 阀 接 口	PRESSURE GAUGE CONNECTION 压 力 表 接 口
0.3/0.8	1687	500	DN65	DN65	Rc3/4	R21/2	M14×1.5	5.0/1.3 II	3949	1300	DN100	DN100	Rc1-1/2	R23/4	M20×1.5
0.3/1.0	1687	500	DN65	DN65	Rc3/4	R21/2	M14×1.5	6.0/0.8	3283	1600	DN100	DN100	Rc1-1/2	R21	M20×1.5
0.3/1.3	1687	500	DN65	DN65	Rc3/4	R21/2	M14×1.5	6.0/1.0	3285	1600	DN100	DN100	Rc1-1/2	R21	M20×1.5
0.6/0.8	2082	650	DN65	DN65	Rc3/4	R21/2	M14×1.5	6.0/1.3	3289	1600	DN100	DN100	Rc1-1/2	R21	M20×1.5
0.6/1.0	2082	650	DN65	DN65	Rc3/4	R21/2	M14×1.5	8.0/0.8	4083	1600	DN150	DN150	Rc2-1/2	R21	M20×1.5
0.6/1.3	2084	650	DN65	DN65	Rc3/4	R21/2	M14×1.5	8.0/1.0	4085	1600	DN150	DN150	Rc2-1/2	R21	M20×1.5
1.0/0.8	2153	800	DN80	DN80	Rc1	R23/4	M14×1.5	8.0/1.3	4089	1600	DN150	DN150	Rc2-1/2	R21	M20×1.5
1.0/1.0	2154	800	DN80	DN80	Rc1	R23/4	M14×1.5	10.0/0.8	4296	1800	DN150	DN150	Rc2-1/2	R21	M20×1.5
1.0/1.3	2156	800	DN80	DN80	Rc1	R23/4	M14×1.5	10.0/1.0	4298	1800	DN150	DN150	Rc2-1/2	R21	M20×1.5
1.5/0.8	2262	1000	DN80	DN80	Rc1-1/4	R23/4	M14×1.5	10.0/1.3	4302	1800	DN150	DN150	Rc2-1/2	R21	M20×1.5
1.5/1.0	2264	1000	DN80	DN80	Rc1-1/4	R23/4	M14×1.5	10.0/0.8 II	5083	1600	DN150	DN150	Rc2-1/2	R21	M20×1.5
1.5/1.3	2266	1000	DN80	DN80	Rc1-1/4	R23/4	M14×1.5	10.0/1.0 II	5085	1600	DN150	DN150	Rc2-1/2	R21	M20×1.5
2.0/0.8	2762	1000	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	10.0/1.3 II	5089	1600	DN150	DN150	Rc2-1/2	R21	M20×1.5
2.0/1.0	2764	1000	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	15/0.8	5354	2000	DN150	DN150	Rc2-1/2	R21	M20×1.5
2.0/1.3	2766	1000	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	15/1.0	5358	2000	DN150	DN150	Rc2-1/2	R21	M20×1.5
3.0/0.8	2930	1200	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	15/1.3	5364	2000	DN150	DN150	Rc2-1/2	R21	M20×1.5
3.0/0.8-08	2930	1200	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	20/0.8	4834	2400	DN200	DN200	Rc3	R21	M20×1.5
3.0/1.0	2932	1200	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	20/1.0	4838	2400	DN200	DN200	Rc3	R21	M20×1.5
3.0/1.0-08	2932	1200	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	20/1.3	4846	2400	DN200	DN200	Rc3	R21	M20×1.5
3.0/1.3	2934	1200	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	20/0.8 II	6854	2000	DN200	DN200	Rc3	R21	M20×1.5
3.0/1.3-08	2934	1200	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	20/1.0 II	6858	2000	DN200	DN200	Rc3	R21	M20×1.5
4.0/0.8	2980	1400	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	20/1.3 II	6864	2000	DN200	DN200	Rc3	R21	M20×1.5
4.0/1.0	2982	1400	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	30/0.8	6704	2500	DN200	DN200	Rc3	R21	M20×1.5
4.0/1.3	2986	1400	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	30/1.0	6710	2500	DN200	DN200	Rc3	R21	M20×1.5
4.0/0.8 II	3930	1200	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	30/1.3	6714	2500	DN200	DN200	Rc3	R21	M20×1.5
4.0/1.0 II	3930	1200	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	40.0/0.8	8101	2600	DN200	DN200	Rc3	R21	M20×1.5
4.0/1.3 II	3934	1200	DN80	DN80	Rc1-1/4	R23/4	M20×1.5	40.0/1.0	8105	2600	DN200	DN200	Rc3	R21	M20×1.5
5.0/0.8	3470	1400	DN100	DN100	Rc1-1/2	R23/4	M20×1.5	40.0/1.3	8113	2600	DN200	DN200	Rc3	R21	M20×1.5
5.0/1.0	3472	1400	DN100	DN100	Rc1-1/2	R23/4	M20×1.5	50.0/0.8	7902	3000	DN200	DN200	Rc3	R21	M20×1.5
5.0/1.3	3478	1400	DN100	DN100	Rc1-1/2	R23/4	M20×1.5	50.0/1.0	7910	3000	DN200	DN200	Rc3	R21	M20×1.5
5.0/0.8 II	3945	1300	DN100	DN100	Rc1-1/2	R23/4	M20×1.5	50.0/1.3	7918	3000	DN200	DN200	Rc3	R21	M20×1.5
5.0/1.0 II	3947	1300	DN100	DN100	Rc1-1/2	R23/4	M20×1.5								

Note :1. The above parameters are for reference only. The final detailed parameters are subject to the specific design drawing.
 2. Including but not limited to the above volume and pressure, the final subject to customer requirements.

备注：1.上述参数仅供外形参考，最终详细参数以具体设计图纸为准。2.包括但不限于上述容积与压力，最终以客户要求为准。